



# Paint

by hemway.

## Premium Interior Paint

A durable matt emulsion for use on walls and ceilings. Surfaces should be cleaned with warm soapy water before coating.

### Applications

- ✓ Walls
- ✓ Ceilings

### Features

- ✓ 118 Colours
- ✓ High Pigmentation
- ✓ Matt
- ✓ Vegan & Cruelty-Free
- ✓ Acrylic
- ✓ Washable
- ✓ Water-Based
- ✓ UV Resistant
- ✓ Eco-Friendly
- ✓ Non-Toxic

### Preparation

Can be applied to most walls and ceilings without sanding or priming and directly over old paint and varnish. Ensure your desired wall or ceiling is clean, free from wax, oil and fully dry. Carry out a sample test in a small area first to ensure it meets your expectations before carrying out your project. Suitable for use with stencils or masking tape.

### Cleaning

Remove excess paint from used tools before washing. Wash brushes and rollers in warm soapy water. Replace lid firmly and store upright to avoid any spillage.

### Important Instructions

- Read and follow SDS, TDS and label instructions.
- Stir all paints thoroughly before use.
- Always use the same batch number on the same job.
- Check colour and sheen. Hemway will not accept any discrepancies arising after use.
- Filter the product immediately before use.
- Reduce emissions and maintain quality by replacing tin lid after use.

Recommended Coats	1 - 2
Mixing	Ready For Use
Drying Time: Touch Dry	1 Hour
Recoatibility / Overcoating	Min. 4 Hours
Wet Film Thickness <sup>1</sup>	100 Microns
Dry Film Thickness <sup>1</sup>	35 Microns
Solids By Volume	35.00%
Flashpoint	>93°C
Storage	Between 5°C and 25°C <sup>2</sup>
Shelf Life	12 Months <sup>3</sup>
Maximum VOC Content	0.009Kg/L
Regulations / Compliance	2004/42 IIA WB (A) 30
Colour Range	Hemway Colour Range

<sup>1</sup> Hemway Technical Data Sheets indicate a Dry Film Thickness that will be achieved when applying a particular Wet Film Thickness. These values are a guide only and are not to be used as specifications. Film thickness will vary depending on actual use and specification. Great care should be taken to achieve the DFT stated in the agreed specification and to avoid areas of excessively low or high thickness.

<sup>2</sup> When not in use, cans must be kept sealed.

<sup>3</sup> From delivery date, in original sealed containers.