



# Lacquer

by hemway.

## Premium Clear Gloss Lacquer

Clear Gloss Lacquer is designed to enhance and protect painted surfaces, preventing stains, marks, color fading, and any unwanted wear and tear on a paint-finished surface. With a high-gloss finish, Clear Gloss Lacquer adds a sleek, sophisticated look, bringing out the vibrancy of the underlying color while delivering a smooth, reflective surface.

### Applications

- ✓ Furniture
- ✓ Painted Surfaces
- ✓ Walls
- ✓ Interior and Exterior

### Features

- ✓ Gloss Finish
- ✓ Long-Lasting
- ✓ Multi-Surface
- ✓ Water-Based
- ✓ Eco-Friendly
- ✓ Highly Protective
- ✓ Vegan & Cruelty-Free
- ✓ Water Resistant
- ✓ UV Resistant
- ✓ Non-Toxic

### Preparation

Hemway Clear Gloss Lacquer requires no sanding or priming before use. Simply stir the tin and apply the lacquer to your surface. For outdoor projects, ensure the surface is completely dry and that you apply the lacquer in dry conditions to prevent moisture from being trapped under the coating.

### Cleaning

After use, immediately clean any excess lacquer from your tools. Wash with warm, soapy water. Make sure the tin is properly sealed and stored upright to prevent spills or the lacquer drying out.

### Important Instructions

- Read and follow SDS, TDS and label instructions.
- Stir all paints thoroughly before use.
- Check colour and sheen.
- Reduce emissions and maintain quality by replacing tin lid after use.

|                                 |   |
|---------------------------------|---|
| Recommended Coats               | 1 - 2   |
| Mixing: Brush / Roller          | Ready For Use                                   |
| Mixing: Spray Gun               | Base: 5L / Thinner: >10%                        |
| Drying Time: Touch Dry          | 30 Minutes at 20°C                              |
| Drying Time: Hard Dry           | 24 Hours  |
| Recoatibility / Overcoating     | Min. 16 Hours / Max. 14 Days                    |
| Wet Film Thickness <sup>1</sup> | 80 Microns                                      |
| Dry Film Thickness <sup>1</sup> | 30 Microns                                      |
| Coverage                        | 12m <sup>2</sup> per L at 30µm DFT <sup>1</sup> |
| Flashpoint                      | 103°C   |
| Storage                         | Between 5°C and 25°C <sup>2</sup>               |
| Shelf Life                      | 12 Months <sup>3</sup>                          |
| Maximum VOC Content             | 0.11Kg/L  |
| Regulations / Compliance        | 2004/42 IIA WB (A) 30                           |

<sup>1</sup> Hemway Technical Data Sheets indicate a Dry Film Thickness that will be achieved when applying a particular Wet Film Thickness. These values are a guide only and are not to be used as specifications. Film thickness will vary depending on actual use and specification. Great care should be taken to achieve the DFT stated in the agreed specification and to avoid areas of excessively low or high thickness.

<sup>2</sup> When not in use, cans must be kept sealed.

<sup>3</sup> From delivery date, in original sealed containers.