

PRODUCT NAME
Hemway Clear Gloss Lacquer

ORIGINALLY ISSUED 01/02/2025
PRODUCT CODE HEMGLOSS

VERSION 1.0
VERSION DATE 01/02/2025

PRODUCT DESCRIPTION
Clear Gloss Lacquer is designed to enhance and protect painted surfaces, preventing stains, marks, color fading, and any unwanted wear and tear on a paint-finished surface. Clear Gloss Lacquer is versatile and can be used both internally and externally, providing flexibility for the user. With a high-gloss finish, Clear Gloss Lacquer adds a sleek, sophisticated look, bringing out the vibrancy of the underlying color while delivering a smooth, reflective surface. As the latest addition to Hemway's Lacquer product range, Clear Gloss Lacquer offers a timeless, elegant feel, and consistently delivers long-lasting, durable results that maintain their brilliance use after use.

IMPORTANT INSTRUCTIONS BEFORE USE

- Read and follow SDS, TDS and label instructions
- Stir all paints thoroughly before use
- Check colour & sheen.
- Reduce emissions and maintain quality by replacing tin lid after use

MAXIMUM VOC CONTENT (RFU)
0.11Kg/L
REGULATIONS / COMPLIANCE
• 2004/42 IIA WB (D) 130

COLOUR RANGE

GENERAL INFORMATION

Coverage	12 square metres per litre @ 30 microns dft
Flashpoint	103°C
Storage	Store between 5°C - 25°C. When not in use, cans must be kept sealed
Shelf Life	12 months from delivery date in original sealed containers

CLEANING
Ensure your desired surface area is clean, free from wax, oil and fully dry. Carry out a sample test in a small area first, this will ensure it meets your expectations before carrying out your full project.



SURFACE PREPARATION
With the lid securely on, shake the tin well, then stir the contents of this tin with a thin spatula. This will ensure an even mixture is accomplished. We recommend using a brush or roller. Load your applicator with Clear Gloss Lacquer, and then remove excess before applying. If using a brush, use a 2-3 inch paintbrush, applying a crisscross motion to give an even spread. Allow 1 hour to dry between coats.

ADDITIONAL INFORMATION

HEALTH AND SAFETY
• Refer to SDS and tin label prior to use.

APPLICATION METHODS

	BRUSH	ROLLER	COMPLIANT SPRAY GUN	
MIXING RATIO				
RFU		RFU	Base Thinner	5ltr >10%
THINNER OPTIONS			Water	Water
VISCOSITY	As supplied	As supplied	As supplied	
NUMBER OF COATS (GUIDE ONLY)	1-2 Coats	1-2 Coats	1-2 Coats	
FLASH OFF				
DRYING TIME	Touch dry Hard dry	30mins @20°C 24 hours	Touch dry Hard dry	30mins @20°C 24 hours
RECOATABILITY / OVERCOATING	16hrs minimum 14days maximum	16hrs minimum 14days maximum	16hrs minimum 14days maximum	

	WET FILM THICKNESS*			
	80microns	80microns	80microns	
	DRY FILM THICKNESS*			
	30microns	30microns	30microns	
<small>* Hemway Technical Data Sheets indicate a Dry Film Thickness that will be achieved when applying a particular Wet Film Thickness. These values are a guide only and are not to be used as specifications. Film thickness will vary depending on actual use and specification. Great care should be taken to achieve the dft stated in the agreed specification and to avoid areas of excessively low or high thickness.</small>				

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of Hemway's knowledge and belief accurate and reliable as of the date indicated. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy themselves as to the suitability and completeness of such information for their own particular use.